

## General Rules

1. Safety First
2. Drawbars must be stationary in all directions
3. Hitch hole must measure a minimum of 3in. Wide and 3.5 in. long.
4. If a drawbar is adjusted, it must be rechecked.
5. No pulling directly off wishbone.
6. An opening of 10 in. wide and 18 in. above the drawbar is required to be free of weights for the safety of the person hooking and unhooking.
7. Weights can be 2 foot ahead of the front of the tractor and no more than 4 ft. 9 in. from the center of the rear axle to the back of the weight.
8. Must run a stock appearing manifold.
9. No drooping clevis.
10. Each tractor has two attempts to move the sled before 75 ft. or to make adjustments.
11. The first puller has the option to rehook.
12. Any tractor with a steady stream of liquid or dropping weights or parts, while hooked to the sled, will be disqualified.
13. No pulling from lift arms or topline.
14. Tractors have 75 ft to set their speed when using a speed board.
15. If RPM's are in question, the tractor in question and the tractor of the person disputing will both be checked.
16. If driver is under 16 years old, they must have a certificate showing they have successfully completed a credited tractor safety course.
17. Anyone protesting cubic inch or turbo charger limits must put up \$250 for protest. Winner of protest will keep the money.

## Antique Rules

1. Antiques must be Stock appearing and have all components in stock location.
2. No excessive stripping
3. 16.9-28 or 15.5-38 bias ply tires.
4. No altered tires.
5. No torqueing
6. Drawbar must pull from stock attachments.
7. 18 inch drawbar 18 inch back from center of axle
8. Must have working governor.
9. Tractor make and model must have been in production 1958 or before.
10. 3.5 mph pace blacktop and dirt
11. RPM's must be no more than 10% over stock for make and model of tractor. RPM level will be determined by the NATPA RPM chart.
12. Random RPM checks will be made
13. No MSD systems.

## Improved Antiques

1. Antiques must be Stock appearing and have all components in stock location.
2. No excessive stripping

3. 16.9-28 or 15.5-38 bias ply tire.
4. No altered tires.
5. No torqueing
6. Drawbar must pull from stock attachments.
7. 18 inch drawbar 18 inch back from rear axle.
8. Must have working governor.
9. Tractor make and model must have been in production 1958 or before.
10. 4 mph blacktop and dirt
11. 3000 RPM limit.
12. Random RPM checks will be made.
13. No MSD systems.

### **NA Open Farm**

1. Over 3000 RPMs must have safety equipment.
2. 18.4 – 38 tire limit, radial tires allowed.
3. 8 mph pace blacktop & dirt
4. 20 inch drawbar. 18 inch back from center of axle.

### **6250 – 6750 Open Farm**

1. Single Turbo Charger
2. No CID Limit or turbo limit or RPM limit.
3. 20 inch drawbar
4. 8 mph blacktop / no pace dirt
5. Must have safety equipment.

### **8500 – 9000 Open Farm**

1. 3000 RPM Limit
2. 466 CID Limit
3. Turbocharged tractors must run on diesel. Turbo no larger than 2.31 inch inlet without slots or slugs, wheel must protrude into housing. Must have 3/8 inch grade 8 cross bolts.
4. A pump limit
5. No aftermarket intercoolers or ice boxes (If equipped with after market cooler it must be disabled)
6. 18.4 x 38 tire limit. No altered tires.
7. Must have safety equipment.
8. 8 mph pace blacktop. No pace dirt.
9. 20 inch drawbar 18 inches back.

### **9000 / 9500 / 10500 Farm**

1. 3000 RPMs.
2. 414 CID limit. Naturally aspirated (466 CID limit 10,500)
3. 18.4-38 tire limit, no altered tires. (20.8 x 38 limit 10,500)
4. 5 mph blacktop / no pace dirt

5. Stock appearing chassis and front axle
6. Stock appearing cast wheels.
7. 20 inch drawbar, 18 inch back from center of rear axle.
8. Stock appearing injection pump for make and model.

### **9000 / 9500 / NA - 4 Cylinder Turbo Open Farm**

1. 3000 RPMs
2. No CID Limit / 4 cylinder turbos allowed
3. 18.4 – 38 Tire Limit, No altered tires.
4. 8 mph pace blacktop & dirt
5. 20 inch drawbar
6. Pressed steel wheels allowed

### **12000 & 13000 Farm**

1. 20.8-38 or 18.4-42 tire limit, no altered tires.
2. Stock appearing cast wheels.
3. 20 inch drawbar, 18 inch back from center of rear axle.
4. Stock appearing chassis and front axle.
5. Box 3LM with no larger than 2.31 inch inlet without slugs or slots, wheel must protrude into the housing. Must bolt to exhaust housing with no modification to charger or manifold.
6. No water injection.
7. Naturally aspirated and tractors with 466 or less CID from the factory can run 3000 RPMs.
8. V8's between 467-540 CID are limited to stock CID and 2600 RPMs.
9. Inline 6 cylinders between 467-540 CID are limited to stock CID and 2500 RPMs
10. 8 mph pace blacktop, no pace dirt

### **12500 & 14000 Open Farm**

1. 3000 RPM limit
2. 8 mph pace blacktop, no pace dirt

### **Powder Puff**

1. Driver must be able to enter and exit track by themselves.